

MATERIAL SAFETY DATA SHEET

Bio Chem, Inc.
P.O. Box 521925
SLC, UT84152 - USA



GENERAL INFORMATION NUMBER: 1-800-653-9795

REVISION DATE: September 23, 2002
DATE OF ISSUE: October 15, 2002

I - Product Identification

Odor Ban

PRODUCT CODE: 0325

CHEMICAL FORMULATION: Solvent based cleaner.

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 2 FLAMMABILITY: 2 REACTIVITY: 0
HAZARD RATING: 4 - Extreme; 3 - High; 2 - Moderate; 1 - Slight; 0 - Insignificant

II - Hazardous Ingredients

Values reported as TWA unless noted.

SUBSTANCE	APPROX	OSHA	ACGIH	EPA 40 CFR:			CAS #
	%	PEL	TLV	302	355	372	
Monochlorotoluene	> 95.0	50 ppm	50 ppm	N	N	N	95-49-8

Key: PEL: Permissible Exposure Limit TLV: Threshold Limit Value C: Ceiling level STEL: Short Term Exposure Limit
N/A: Not Applicable N/D: Not Determined N/E: Not Established Y: Yes N: No
302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).
355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).
372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

III - Physical Data

BOILING POINT (°F): N/D SPECIFIC GRAVITY (WATER = 1): 1.079
VAPOR PRESSURE (mm Hg): N/D VOC CONTENT (% by weight): > 95.0
VAPOR DENSITY (AIR = 1): N/D EVAPORATION RATE (WATER = 1): > 1.0
SOLUBILITY IN WATER: Emulsifiable pH: N/A
APPEARANCE AND ODOR: Clear, slight yellow liquid; chlorinated solvent odor.

IV - Fire and Explosion Hazard Data

FLASH POINT (°F): 118 (TEST METHOD): Closed cup
FLAMMABLE LIMITS IN AIR (VOLUME %) UPPER: N/D LOWER: N/D
EXTINGUISHING MEDIA: Foam, carbon dioxide, dry chemical.
SPECIAL FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water fog. Firefighters should be equipped with full protective gear including self-contained breathing apparatus. Avoid breathing vapors or fumes as fire may produce hazardous vapors.
UNUSUAL FIRE AND EXPLOSION HAZARD: Vapors may cause flashback. May release hydrogen chloride when heated.

DIRECTIONS:

To degrease and deodorize sewer mains, laterals, wet wells, pumping stations and equipment, drip or dispense into the flow at the rate of 4 to 20 parts per million.

To degrease lift stations or open restricted sewer lines, drains or traps, pour directly into the drain or opening as close to the restriction as possible. Follow with a warm water flush, if possible.

To deodorize aerators, digesters, filters, drying beds, dumps and landfills, dilute 1:50 with water and spray liberally over the source of all odors.

ODOR BAN

DEGREASER

AND

DEODORIZER

FOR

LIFT STATIONS

SEWERS, AND

TREATMENT PLANTS

CAUTION — COMBUSTIBLE
Harmful or fatal if swallowed. Keep away from heat or open flame. See side panel for further cautions and first aid instructions.
KEEP OUT OF REACH OF CHILDREN

Sold by:

CAUTION — COMBUSTIBLE
Harmful or fatal if swallowed. Keep away from heat or open flame. Contains chlorinated hydrocarbons. Avoid contact with eyes, skin, or clothing. Avoid prolonged breathing of vapor. Use only with adequate ventilation.

FIRST AID:

External - Wash thoroughly with soap and water.
Internal - Drink large quantities of water. Do not induce vomiting. Call physician or poison control center immediately.

Eyes - Flush eyes and under eyelids with plenty of cool water for at least 15 minutes, and obtain medical attention.
KEEP OUT OF REACH OF CHILDREN
32582037

NET CONTENTS: