

TAR & ASPHALT REMOVER

This powerful solvent cleaner is recommended for removal of road tar, asphalt and grease from all municipal equipment, concrete floors and metal parts. It works effectively to clean boat and ship bilges and removes sludge from oil tanks. Used by roofing and blacktop contractors to clean tools, equipment and work areas.

DIRECTIONS

Apply to the affected area with a hand sprayer or by wiping or swabbing onto surface to be cleaned. Allow sufficient time to penetrate and dissolve the deposits, then, rinse off emulsified soils with water under pressure.

To clean parts or remove light deposits, cleaner may be diluted with 4 to 8 parts of another solvent such as mineral spirits or kerosene.

NOTE: Use with care on automotive finishes to prevent damage to air-dried paint and delicate surfaces.

DISSOLVES & EMULSIFIES
GREASE, TAR & ASPHALT

POWERFUL

FAST ACTING

HOSES OFF WITH WATER

CAUTION – COMBUSTIBLE

Harmful or fatal if swallowed. Keep away from heat or open flame. See side panel for further cautions and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

Sold By:

CAUTION – COMBUSTIBLE

Harmful or fatal if swallowed. Keep away from heat or open flame. Contains chlorinated hydrocarbons. Avoid contact with eyes, skin or clothing. Avoid prolonged breathing or vapor. Use only with adequate ventilation.

FIRST AID

External: Wash thoroughly with soap and water.

Internal: Drink large quantities of water. Call a physician or poison control center immediately.

Eyes: Flush eyes and under eyelids with plenty of cool water for least 15 minutes and obtain medical attention.

KEEP OUT OF REACH OF CHILDREN

This product contains	CAS Number
2-chlorotoluene.	25168-05-2

32591300

NET CONTENTS:

5 6 20 30 55
GALLONS