

MATERIAL SAFETY DATA SHEET

Bio Chem, Inc.
P.O. Box 521925
SLC, UT84152 - USA



GENERAL INFORMATION NUMBER: 1-800-653-9795

REVISION DATE: September 23, 2002

DATE OF ISSUE: October 15, 2002

I - Product Identification

Paint & Varnish Remover

PRODUCT CODE: 0330

CHEMICAL FORMULATION: Thickened Solvent Blend

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 3

FLAMMABILITY: 1

REACTIVITY: 0

HAZARD RATING: 4 - Extreme; 3 - High; 2 - Moderate; 1 - Slight; 0 - Insignificant

II - Hazardous Ingredients

Values reported as TWA unless noted.

SUBSTANCE	APPROX %	OSHA PEL	ACGIH TLV	EPA 40 CFR:			CAS #
				302	355	372	
Methylene Chloride	> 80.0	350 ppm	350 ppm	Y	Y	N	75-09-2
Methanol	> 5.0	200 ppm	200 ppm	N	N	N	67-56-1

Key: PEL: Permissible Exposure Limit TLV: Threshold Limit Value C: Ceiling level STEL: Short Term Exposure Limit
N/A: Not Applicable N/D: Not Determined N/E: Not Established Y: Yes N: No
302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).
355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).
372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

III - Physical Data

BOILING POINT (°F): 300
VAPOR PRESSURE (mm Hg): N/A
VAPOR DENSITY (AIR = 1): N/A
SOLUBILITY IN WATER: Insoluble
APPEARANCE AND ODOR: Viscous pink, opaque liquid, chlorinated solvent odor.
SPECIFIC GRAVITY (WATER = 1): 1.26
VOC CONTENT (% by weight): > 90
EVAPORATION RATE (WATER = 1): > 1.0
pH: N/A

IV - Fire and Explosion Hazard Data

FLASH POINT (°F): > 200 (TEST METHOD): Closed cup
FLAMMABLE LIMITS IN AIR (VOLUME %) UPPER: N/A LOWER: N/A
EXTINGUISHING MEDIA: Foam, carbon dioxide, dry chemical.
SPECIAL FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water fog. Firefighters should be equipped with full protective gear including self-contained breathing apparatus.
UNUSUAL FIRE AND EXPLOSION HAZARD: None

V - Reactivity Data

STABILITY: Stable**INCOMPATIBILITY:** Strong acids and oxidizing agents.**CONDITIONS TO AVOID:** High temperatures**HAZARDOUS DECOMPOSITION PRODUCTS:** Thermal decomposition may produce oxides of carbon, HCL, and chlorine gas.**HAZARDOUS POLYMERIZATION:** Will not occur.**CONDITIONS TO AVOID:** None

VI - Health Hazard Data

ROUTES OF ENTRY **INHALATION:** X **EYE CONTACT:** X **SKIN CONTACT:** X **INGESTION:** X**INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS:** None**EFFECTS OF OVEREXPOSURE****IF IN EYES:** Irritation, tearing, redness, blurred vision.**IF SWALLOWED:** Gastrointestinal irritation, nausea, vomiting, diarrhea.**IF INHALED:** Respiratory tract irritation, dizziness, headache, nausea, narcosis, euphoria.**EMERGENCY AND FIRST AID PROCEDURES****IF IN EYES:** Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.**IF ON SKIN:** Remove contaminated clothing and launder before re-use. Wash with soap and water. If irritation persists, obtain medical attention.**IF SWALLOWED:** Contact physician or poison control center immediately. Give affected person several glasses of water and induce vomiting. Never give anything by mouth to an unconscious person.**IF INHALED:** Remove person to fresh air. Perform artificial respiration if indicated. Obtain medical assistance. Do not give stimulants.

VII - Spill or Leak Protection

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Extinguish all sources of ignition and ventilate area. Soak up spilled material with inert absorbent material and place in closed container for disposal. Wash floor to remove sticky residue.**WASTE DISPOSAL METHOD:** Consult local environmental authorities.

VIII - Special Protection Information

RESPIRATORY PROTECTION: Use with adequate ventilation. If recommended Exposure Limits are exceeded wear a NIOSH approved respirator, following manufacturer's recommendations.**VENTILATION****LOCAL:** Recommended**MECHANICAL:** Recommended**PROTECTIVE GLOVES:** Chemical resistant.**EYE PROTECTION:** Safety glasses.**OTHER PROTECTIVE EQUIPMENT:** Protective clothing, emergency shower and eye wash station.**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Store in a cool, dry place away from heat or open flame.

Keep container tightly closed when not in use.

OTHER PRECAUTIONS: Keep out of reach of children.

IX - Transportation Information (ground transportation only)

DOT PROPER SHIPPING NAME: None**DOT CLASS:** None**DOT ID NUMBER:** None**DOT PACKING GROUP:** NoneThe shipping information listed above applies only to non-bulk (< 119 gallons) containers of this product. This product may have more than one proper shipping name depending on packaging, product properties, & mode of shipment. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may apply.

REVISION DATE: April 17, 2002**Prepared by:** PMR**DATE OF ISSUE:** April 18, 2002

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Athea Laboratories, Inc. assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.

This thick-bodied, industrial strength stripper is ideal for removing a wide variety of finishes from most surfaces. The special thickened formula allows it to be used effectively on vertical surfaces, and provides a vapor barrier for faster penetration and removal of finishes.

DIRECTIONS: Use this product outdoors if possible. For indoor use, open all windows and doors or use other means to provide fresh air movement during use. Do not use in basement or other unventilated areas.

Open container carefully and close tightly after each use. Clean up rags, papers and other waste promptly. Allow solvent to evaporate, then dispose of waste in metal containers.

This product may be used in a stripping tank, or mopped, sprayed or brushed onto surface. Apply stripper in a heavy continuous coat, and allow to act until finish is blistered and lifted. Remove the softened finish by scraping or with high pressure water blast.

**DO NOT HEAT STRIPPER.
DO NOT USE ON ASPHALT,
RUBBER, OR PLASTIC.**

PAINT & VARNISH REMOVER

**QUICKLY REMOVES ALL PAINTS
VARNISH, SHELLAC, SEALS AND
FINISHES AND SCOTCH LITE®**

SAFE TO USE ON:

- Wood and Metal Surfaces
- Concrete, Stone and Terrazzo
- Ceramic and Plaster Interiors



**DANGER POISON
MAY BE FATAL OR CAUSE BLINDNESS
IF SWALLOWED. VAPOR HARMFUL.**

See side panel for further cautions
and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

Sold by:



**DANGER POISON
MAY BE FATAL OR CAUSE
BLINDNESS IF SWALLOWED.
VAPOR HARMFUL.**

Contains methanol and methylene chloride, which has been shown to cause cancer in certain laboratory animal tests. Risk to your health depends on level and duration of exposure. Cannot be made non-poisonous. Use only in well ventilated area according to directions given above. Vapors and liquid may irritate eyes, skin, and mucous membranes. Wear eye protection and rubber gloves when handling.

FIRST AID:

Internal - Call physician or poison control center immediately. Give person several glasses of water and induce vomiting, and obtain immediate medical attention.
External - Remove contaminated clothing and launder before reuse. Wash skin thoroughly with soap and water. If irritation persists, obtain medical attention.
Eyes - Flush eyes and under eyelids with plenty of water for at least 15 minutes, and obtain immediate medical attention.

KEEP OUT OF REACH OF CHILDREN
33081208

NET CONTENTS: