

EPOXY 3 COMPONENT PATCH

EPOXY FLOOR TOPPING OR PATCHING SYSTEM

100% SOLIDS EPOXY FILLER

CAUTIONARY INFORMATION:

DO NOT USE THIS PRODUCT BEFORE READING THE MATERIAL SAFETY DATA SHEET. FOR INDUSTRIAL/PROFESSIONAL USE ONLY. DO NOT TRANSFER TO UNMARKED CONTAINERS. KEEP OUT OF REACH OF CHILDREN.

CAUTION! Follow all cautionary information contained on 10-22 EPOXY 3 COMPONENT PATCH MIX A and 10-22 EPOXY 3 COMPONENT PATCH MIX B labels and MSDS sheets.

EPOXY 3 COMPONENT PATCH is a unique and complete epoxy mortar system. Usage is simple even under the most extreme conditions. When mixed, EPOXY 3 COMPONENT PATCH provides a high strength patching mortar, which can be feather-edged.

EPOXY 3 COMPONENT PATCH is unique in its ability to bond to damp surfaces. Thus EPOXY 3 COMPONENT PATCH may be used in basements, outdoors, or on slabs where it is difficult, if not impossible, to get the surfaces absolutely dry.

COMPLETE WITH AGGREGATE.
NOTHING ELSE TO ADD

DIRECTIONS:

Clean surfaces of loose aggregate, dust, dirt, grease, and oil. For best results, wash surface with 10% Muriatic Acid and flush with clean water. Allow to dry.

Scientifically designed to fill in and resurface cracks, holes, and pits in wood, concrete, metal, brick and any other surface such as curbing and steps. EPOXY 3 COMPONENT PATCH can also be used for anchoring equipment, posts, parking meters and signs.

Recommendations for the use of this product are based on reliable tests. No guarantee of results are implied where conditions are beyond our control. Under no circumstances or conditions, either expressed or implied, will the manufacturer be liable for damages in excess of the purchase price of this product.
