

# COAL TAR EPOXY 3 COMPONENT PATCH

## Coal Tar Epoxy Mortar Mix

*PERMANENT 100% SOLIDS EPOXY FILLER AND BONDING COMPOUND • 100% SOLID BASED COMPOUND DOES NOT CONTAIN ANY CEMENT*

---

### CAUTIONARY INFORMATION:

---

DO NOT USE THIS PRODUCT BEFORE READING THE MATERIAL SAFETY DATA SHEET. FOR INDUSTRIAL/PROFESSIONAL USE ONLY. DO NOT TRANSFER TO UNMARKED CONTAINERS. KEEP OUT OF REACH OF CHILDREN.

**CAUTION! HARMFUL IF SWALLOWED. KEEP OUT OF REACH OF CHILDREN.**

**COAL TAR EPOXY 3 COMPONENT PATCH** is a unique and complete epoxy mortar system. Usage is simple even under the most extreme conditions. When mixed, **COAL TAR EPOXY 3 COMPONENT PATCH** provides a high-strength patching mortar, which can be feather-edged.

**COAL TAR EPOXY 3 COMPONENT PATCH** is unique in its ability to bond to damp surfaces. Thus **COAL TAR EPOXY 3 COMPONENT PATCH** may be used on any asphaltic surface where it is difficult, if not impossible to get the surface absolutely dry.

Complete with aggregate. Nothing else to add.

---

### DIRECTIONS

---

Clean surfaces of loose aggregate, dirt, grease, and oil. Pour all of container B into container A. Mix A into B. Use paint-type mechanical mixer when possible. Then put sand into mix, mixing thoroughly. Spread on area, smooth and finish. Pot life approximately 60 minutes.

Scientifically designed to fill in and resurface cracks, holes, and pits in any asphaltic surface, roof, driveway or parking lot and any other surface such as curbing and steps. **COAL TAR EPOXY 3 COMPONENT PATCH** can also be used for anchoring equipment, posts, parking meters and signs.

---

Recommendations for the use of this product are based on reliable tests. No guarantee of results are implied where conditions are beyond our control. Under no circumstances or conditions, either expressed or implied, will the manufacturer be liable for damages in excess of the purchase price of this product.

---