

WATER STOP CEMENT

STOPS RUNNING WATER THROUGH CRACKS AND HOLES IN CONCRETE OR MASONRY

CAUTIONARY INFORMATION:

DO NOT USE THIS PRODUCT BEFORE READING THE MATERIAL SAFETY DATA SHEET. FOR COMMERCIAL, INDUSTRIAL, OR PROFESSIONAL USE ONLY. DO NOT TRANSFER TO UNMARKED CONTAINERS. KEEP OUT OF REACH OF CHILDREN.

WARNING: Use rubber gloves: prolonged contact with **WATER STOP CEMENT** may cause skin irritation.

DIRECTIONS:

MIXING: Thoroughly mix **WATER STOP CEMENT** with water until a stiff putty like consistency is reached. Mix only enough **WATER STOP CEMENT** that can be placed in one minute.

SURFACE PREPARATION: Areas to be patched or filled should be dampened with water prior to the application of **WATER STOP CEMENT**.

APPLICATION: Apply with rubber gloves or trowel, to plug leaks, fill cracks and voids.

CURING: To cure filled or patched surfaces dampen initial set. For ultimate strengths cover with curing compound, polyethylene; or by periodic sprays or water for at least one day. Mix **ONLY** with water.

CLEAN UP: Clean tools and equipment with water immediately after use.

Recommendations for the use of this product are based on reliable tests. No guarantee of results are implied where conditions are beyond our control. Under no circumstances or conditions, either expressed or implied, will the manufacturer be liable for damages in excess of the purchase price of this product.
