

100% SOLIDS EPOXY

EPOXY NON-SLIP

NON-SKID SAFETY COATING

bonds permanently to

• CONCRETE

• TILE

• METALS

• TERRAZZO

• WOOD

• SLATE

Easy to apply!

Gives professional results!

DIRECTIONS

Clean floor by acid etching with 15% solution of muriatic acid, removing surface grease, oil, etc. Remove component A & B from container. Blend part A & B for 3 to 5 minutes. Spread a thin uniform coat over area to be treated preferably by trowel and finish with a brush if necessary.

USES

Steps	Entranceways
Ramps	Loading Docks
Exits	Marine Docks
Catwalks	Flat Beds
Fire Stairs	
Equipment	

CAUTION: EPOXY NON-SLIP contains an alkaline amide. Avoid contact with skin and eyes. In case of contact wash with soapy water. Use goggles and gloves recommended.

COMPLETE WITH AGGREGATE
NOTHING ELSE TO ADD.

EPOXY NON-SLIP is a unique non-skid safety coating designed to accident-proof areas where operational conditions such as oil, grease, water and ice reduce the normal traction needed for safety. A special 100% solids epoxy formulation that stands up to even steel-wheeled vehicles and provides a permanent and easy to maintain non-skid coating. Ease of application & excellent coverage make EPOXY NON-SLIP the economical solution to any slipproofing problem.

WAREHOUSE