

EPOXY BROADCAST NON-SLIP

NON-SKID SAFETY COATING

BONDS TO CONCRETE • METALS • WOOD • TILE • TERRAZZO • SLATE

CAUTIONARY INFORMATION:

1. DO NOT USE THIS PRODUCT BEFORE READING THE MATERIAL SAFETY DATA SHEET. DO NOT TRANSFER TO UNMARKED CONTAINERS. FOR INDUSTRIAL AND PROFESSIONAL USE ONLY. KEEP OUT OF REACH OF CHILDREN.

2. CAUTION: Follow all cautionary information contained on **20-22 EPOXY BROADCAST NON-SLIP MIX A** and **20-22 EPOXY BROADCAST NON-SLIP MIX B** labels and MSDS sheets.

IMPORTANT:

**MATERIAL IN THIS CONTAINER IS NOT READY FOR USE.
FOLLOW MIXING DIRECTIONS BELOW BEFORE USING.**

EPOXY BROADCAST NON-SLIP is a unique non-skid safety coating designed to accident-proof areas where operational conditions such as oil, grease, water and ice reduce the normal traction needed for safety. A special epoxy formulation that stands up and provides an easy to maintain non-skid coating. Ease of application and excellent coverage make **EPOXY BROADCAST NON-SLIP** the economical solution to any slipping problem.

DIRECTIONS:

Clean floor by acid etching with 15% muriatic acid removing surface grease, oil, etc. Remove components A & B from container. Blend Part A & B for 3 to 5 minutes. Spread a thin uniform coat over area. Broadcast Non-Slip aggregate over wet area. Coat again as necessary. Each unit will cover 600 square feet, depending on surface.

USES INCLUDE:

- Steps
- Fire stairs
- Marine decks
- Ramps
- Equipment
- Flat beds
- Exits
- Entrance ways
- Catwalks
- Loading docks

**COMPLETE WITH AGGREGATE - NOTHING ELSE TO ADD.
EASY TO APPLY! GIVES PROFESSIONAL RESULTS**

Recommendations for the use of this product are based on reliable tests. No guarantee of results are implied where conditions are beyond our control. Under no circumstances or conditions, either expressed or implied, will the manufacturer be liable for damages in excess of the purchase price of this product.