

RESIN NON-SLIP

NON-SKID SAFETY COATING

CAUTIONARY INFORMATION:

1. CONSULT THE MATERIAL SAFETY DATA SHEET. DO NOT TRANSFER TO UNMARKED CONTAINERS. FOR INDUSTRIAL/PROFESSIONAL USE ONLY. KEEP OUT OF REACH OF CHILDREN.

2. WARNING: Liquid and vapor can cause irritation to the eyes, skin and respiratory tract. Repeated skin contact can cause defatting and dermatitis. Inhalation can cause nausea and headache, possible unconsciousness and even asphyxiation. Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration into lungs can cause chemical pneumoconiosis which may be fatal. Reports have associated repeated and prolonged exposure to anemia, liver abnormalities, kidney damage, eye damage and cardiac abnormality.

3. FIRST AID: In case of skin contact, wash thoroughly with soap and water; for eye contact flush immediately with plenty of water for fifteen (15) minutes and call a physician. If affected by inhalation, remove to fresh air, administer oxygen if necessary and see a physician. If mix is swallowed, do not induce vomiting and see a physician immediately.

4. SAFETY: Rubber gloves and/or barrier creams, protective clothing, goggles and a NIOSH/MSHA approved respirator (if TLV is exceeded) should be worn. Provide sufficient mechanical and/or local exhaust ventilation to maintain exposure below TLV's.

5. DISPOSAL: In case of spillage, absorb and dispose of in accordance with applicable federal, state and local regulations.

6. SPECIAL PRECAUTIONS: Since emptied containers retain product residues (vapor, liquid, and/or solid) extreme caution should still be exercised in their handling. Keep out of reach of children. Not for internal consumption. Prior to use, consult MSDS and read warnings noted on product package for more information.

7. CAUTION: COMBUSTIBLE: Keep from heat or open flame. Avoid prolonged or repeated breathing of vapors and prolonged or repeated contact with skin. Use with adequate ventilation. Do not take internally. Before smoking, eating or after using, cleanse hands thoroughly. Keep container closed.

HIGH SOLIDS, CHEMICALLY RESISTANT. BONDS PERMANENTLY TO CONCRETE, TILE, METALS, TERRAZZO, WOOD AND SLATE. EASY TO APPLY, GIVES PROFESSIONAL RESULTS.

Resin Non-Slip is a unique non-skid safety coating designed to accident-proof areas where operational conditions such as oil, grease, water, ice and chemical spillage reduce the normal traction needed for safety. A special chemically resistant high solids formulation that stands up to even steel-wheeled traffic indoors or outside. Ease of application and excellent coverage make **Resin Non-Slip** the economical and permanent solution to any slipproofing problem.

For use on steps, ramps, exits, catwalks, fire stairs, equipment, entrance ways, loading docks, marine decks and flat beds.

DIRECTIONS:

- Clean surface with heavy duty cleaner degreaser, rinse and allow to dry.
- Mix **Resin Non-Slip** with low speed mixer (electric drill type) or by hand for 3-5 minutes.
- Apply to surface with roller or squeegee. (Do not apply over 50 mls. thickness).

Recommendations for the use of this product are based on reliable tests. No guarantee of results are implied where conditions are beyond our control. Under no circumstances or conditions, either expressed or implied, will the manufacturer be liable for damages in excess of the purchase price of this product.
