

# CHUCK HOLE FILLER

---

## CAUTIONARY INFORMATION:

---

**FOR PROFESSIONAL, COMMERCIAL,  
INSTITUTIONAL AND  
INDUSTRIAL USE ONLY**

**CAUTION:  
KEEP OUT OF REACH OF CHILDREN**

---

## DIRECTIONS:

---

Clean area to be patched. Remove all loose particles, mud, dust, grass, etc. Use stiff broom. Then hose down thoroughly and allow to dry. Open can of **CHUCK HOLE FILLER** and empty into area to be patched. Level **CHUCK HOLE FILLER** by spreading with shovel, board or rake. Fresh **CHUCK HOLE FILLER** should be leveled about 1 inch higher than surrounding pavement to allow for compaction. A minimum final thickness of 2" is recommended.

After area to be patched is filled, tamp with hand tamper, garden roller, or any heavy flat object that will firmly compact the material. The more compaction, the better the patch. The newly paved area may normally be used immediately after being thoroughly compacted. However certain conditions, such as high temperatures, could delay the immediate use of area of traffic.

---

Recommendations for the use of this product are based on reliable tests. No guarantee of results are implied where conditions are beyond our control. Under no circumstances or conditions, either expressed or implied, will the manufacturer be liable for damages in excess of the purchase price of this product.

---