

MATERIAL SAFETY DATA SHEET

Bio Chem, Inc.
P.O. Box 521925
SLC, UT84152 - USA



GENERAL INFORMATION NUMBER: 1-800-653-9795

REVISION DATE: February 25, 2002
DATE OF ISSUE: February 25, 2002

TUFFCRETE 10-44 LIQUID - TUFFLEX 10-55 LIQUID - #10-44 POLYESTER PATCH LIQUID - #10-44LT POLYESTER PATCH LOW TEMP LIQUID - #10-55 POLYESTER LIQUID - #20-00 POLYESTER NON-SLIP LIQUID - #10-66RP POLYESTER ASPHALT PATCH LIQUID
SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT	NTP/IARC/ OSHA CARC.	PERCENT	TLV PPM mg/M ³	LEL	VAPOR PRESSURE	
Styrene Monomer CAS #100425	No	< 50	100 (OSHA)	-	1.1	5 mm/Hg
N,N-Dimethylaniline CAS #121697	No	0.2	5 (Skin)	-	NA	1 mm/Hg

SECTION III: PHYSICAL DATA

BOILING RANGE 295-300°F VAPOR DENSITY HEAVIER LIGHTER. THAN AIR
EVAPORATION RATE FASTER SLOWER. THAN ETHER PERCENT VOLATILE BY VOLUME < 50 WEIGHT PER GALLON 9.3 Lbs.

SECTION IV: FIRE AND EXPLOSION DATA

DOT Category: Flammable Flash Point: 96°F. LEL: 1.0%
Extinguishing Media: Regular foam, carbon dioxide or dry chemical.
Special Firefighting Procedures: Self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode.
Unusual Fire & Explosion Hazards: Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
Hazardous Decomposition Products: May form toxic materials - carbon dioxide and carbon monoxide, various hydrocarbons, etc.